



archlit reserves the right to make changes without prior notice. (11.08.2017)

Surprise Recessed Trimless Continuous lighting fixture that incorporates to a drywall ceiling, with flanges at the sides of 1" (so mud do not crack over time). A continuous diffuser, snaps in allowing runs based on a max of 4' (max logical segments to ship and manipulate at any job site). Runs will look continuous with multiple segments aligned. Installation can be horizontal (ceiling) or vertical (walls). Special angles upon request. Surprise Dry is a 5/8" height fixture that allow to be attached to studs. In different widths of 4", 6" or 8". Dimmable and no dimmable versions. Only for spaces with 5/8" drywall.

Surprise Dry Trimless in 4", 6" and 8" width

SDTsWW

Surprise Dry Trimless We Work

Color Temperature

- 27 - 2700 K
- 30 - 3000 K
- 40 - 4000 K

Finish

- WH - White
 - BK - Black
 - CU - Custom
- Specify RAL color
Only internal and flanges that will be covered in mud

Dimming Options

- O - Non Dimmable 120v
- 1 - Non Dimmable 277v
- 4 - Dimmable 0-10v (4wires, 120/277 v)



Control System

NC - No control

CY - Control on each driver

Control system to manage lighting with Bluetooth technology programmed by end user at site with mesh of fixtures and security levels

Runs

A4 - 4" wide module of 1' nominal 14 w /foot

B4 - 4" wide module of 2' nominal 14 w /foot

C4 - 4" wide module of 3' nominal 14 w /foot

D4 - 4" wide module of 4' nominal 14 w /foot

A6 - 6" wide module of 1' nominal 17.5 w /foot

B6 - 6" wide module of 2' nominal 17.5 w /foot

C6 - 6" wide module of 3' nominal 17.5 w /foot

D6 - 6" wide module of 4' nominal 17.5 w /foot

A8 - 8" wide module of 1' nominal 24.5 w /foot

B8 - 8" wide module of 2' nominal 24.5 w /foot

C8 - 8" wide module of 3' nominal 24.5 w /foot

D8 - 8" wide module of 4' nominal 24.5 w /foot

Total Run: (0 ft 0 in)

Notes:

Drivers are remote

Flanges to be covered with mud 1"



